AMENDMENTS TO THE CLAIMS

1.   (currently amended) A system for performing time delay estimation of signals propagating through an environment, comprising:

one or more sensors configured to receive a plurality of signals; ~~and~~

a time delay estimator operative to measure time delays between multiple pairs of the plurality of signals, thereby generating time delay estimation data from the measured time delays,

wherein at least some of the time delays between the multiple pairs of signals are measured at different points in time; and

a data analyzer operative to analyze the time delay estimation data, to generate a statistical distribution of the time delay estimates from the time delay estimation data, and to calculate at least one of the mean, the median, and the mode of the time delay estimation distribution,

wherein the statistical distribution of the time delay estimates comprises a plurality of bins, the plurality of bins including a central bin, and

-3-

WEINGARTEN, SCHURGIN,
GAGNEBIN & LEBOVICI LLP
TEL. (617) 542-2290
FAX. (617) 451-0313

wherein at least one first time delay estimate is associated with the central bin and multiple second time delay estimates are distributed among remaining ones of the bins.

2.   (original) The system of claim 1 wherein, in the event a degree of noise accompanies the multiple pairs of signals, at least some of the noise is non-correlated.

3.   (canceled)

4.   (original) The system of claim 1 wherein the one or more sensors are configured to receive a plurality of successive signals including multiple pairs of successive signals.

5.   (currently amended) The system of claim 4 wherein the ~~system~~ time delay estimator comprises a passive time delay estimation system.

6.   (original) The system of claim 1 wherein the plurality of signals propagate through a predetermined transmission medium within the environment, the predetermined transmission medium being one of a fluid, the earth, and living tissue.

-4-

7.   (original) The system of claim 1 wherein the time delay estimator includes a signal processor operative to perform one or more preprocessing techniques on one or more of the plurality of signals to facilitate a determination of the temporal location of the one or more signals.

8.   (original) The system of claim 7 wherein the temporal location of the one or more signals corresponds to a prominent feature of the one or more signals, the prominent feature being one of a signal peak, a signal valley, a signal energy, and a signal zero crossing.

9.   (original) The system of claim 7 wherein the preprocessing techniques include at least one of a first technique including determining an absolute value of at least one of the plurality of signals, a second technique including match filtering at least one of the plurality of signals, and an instantaneous envelope detection technique.

10.   (canceled)

-5-

11. (currently amended) The system of claim ~~10~~ 1 wherein the multiple second time delay estimates are substantially uniformly distributed among remaining ones of the bins.

12. (original) The system of claim 1 wherein the plurality of signals comprises one of sonar signals, seismic signals, ultrasonic signals, acoustic signals, and electromagnetic signals.

13. (original) The system of claim 1 further including a beamformer configured to receive representations of the plurality of signals, and to provide beams corresponding to the plurality of signals to the time delay estimator.

14. (currently amended) A system for performing time delay estimation of signals propagating through an environment, comprising:

a transmitter configured to transmit multiple signals through the environment, wherein the transmitted signals travel through the environment until they strike at least one object, thereby generating multiple signals reflected from the object;

one or more sensors configured to receive the multiple reflected signals; ~~and~~

-6-

WEINGARTEN, SCHURGIN,
GAGNEBIN & LEBOVICI LLP
TEL. (617) 542-2290
FAX. (617) 451-0313

a time delay estimator operative to receive representations of the transmitted signals, to measure time delays between multiple pairs of signals, each pair comprising a respective reflected signal and a representation of a respective transmitted signal, thereby generating time delay estimation data from the measured time delays,

wherein at least some of the time delays between the multiple pairs of signals are measured at different points in time; and

a data analyzer operative to analyze the time delay estimation data, to generate a statistical distribution of the time delay estimates from the time delay estimation data, and to calculate at least one of the mean, the median, and the mode of the time delay estimation distribution,

wherein the statistical distribution of the time delay estimates comprises a plurality of bins, the plurality of bins including a central bin, and

wherein at least one first time delay estimate is associated with the central bin and multiple second time delay estimates are distributed among remaining ones of the bins.

-7-

15.   (original) The system of claim 14 wherein, in the event a degree of noise accompanies the reflected signals, at least some of the noise is non-correlated.

16.   (canceled)

17.   (currently amended) The system of claim 14 wherein the ~~system~~ time delay estimator comprises an active time delay estimation system.

18.   (original) The system of claim 14 wherein each transmitted signal comprises a sonar ping, and each reflected signal comprises a sonar echo.

19.   (original) The system of claim 14 wherein the multiple transmitted signals propagate through a predetermined transmission medium within the environment, the predetermined transmission medium being one of a fluid, the earth, and living tissue.

20.   (original) The system of claim 14 wherein the time delay estimator includes a signal processor operative to perform one or more preprocessing techniques on one or more of the reflected

-8-

signals to facilitate a determination of the temporal location of the one or more reflected signals.

21. (original) The system of claim 20 wherein the temporal location of the one or more reflected signals corresponds to a prominent feature of the one or more reflected signals, the prominent feature being one of a signal peak, a signal valley, a signal energy, and a signal zero crossing.

22. (original) The system of claim 20 wherein the preprocessing techniques include at least one of a first technique including determining an absolute value of at least one of the plurality of signals, a second technique including match filtering at least one of the plurality of signals, and an instantaneous envelope detection technique.

23. (canceled)

24. (currently amended) The system of claim 23—14 wherein the multiple second time delay estimates are substantially uniformly distributed among remaining ones of the bins.

-9-

25. (original) The system of claim 14 wherein the plurality of signals comprises one of sonar signals, seismic signals, ultrasonic signals, acoustic signals, and electromagnetic signals.

26. (currently amended) A system for performing time delay estimation of signals propagating through an environment, comprising:

a transmitter configured to transmit multiple signals through the environment, wherein the transmitted signals travel through the environment until they strike at least one object, thereby generating multiple signals reflected from the object;

one or more sensors configured to receive the multiple reflected signals;

a time delay estimator operative to receive representations of the transmitted signals, to measure time delays between multiple pairs of signals, each pair comprising a respective reflected signal and a representation of a respective transmitted signal, thereby generating time delay estimation data from the measured time delays,

wherein at least some of the time delays between the multiple pairs of signals are measured at different points in time; and

-10-

~~The system of claim 14 further including~~ a beamformer configured to receive representations of the reflected signals, and to provide beams corresponding to the reflected signals to the time delay estimator.

27. (currently amended) A method of performing time delay estimation of signals propagating through an environment, comprising the steps of:

receiving a plurality of signals by one or more sensors;

measuring time delays between multiple pairs of the plurality of signals by a time delay estimator; ~~and~~

generating time delay estimation data from the measured time delays by the time delay estimator,

wherein at least some of the time delays between the multiple pairs of signals are measured at different points in time;

analyzing the time delay estimation data by a data analyzer;

generating a statistical distribution of the time delay estimates from the time delay estimation data; and

calculating at least one of the mean, the median, and the mode of the time delay estimation distribution,

-11-

wherein the statistical distribution of the time delay estimates comprises a plurality of bins, the plurality of bins including a central bin, and

wherein at least one first time delay estimate is associated with the central bin and multiple second time delay estimates are distributed among remaining ones of the bins.

28. (original) The method of claim 27 wherein, in the event a degree of noise accompanies the multiple pairs of signals, at least some of the noise is non-correlated.

29. (canceled)

30. (original) The method of claim 27 wherein the receiving step includes receiving a plurality of successive signals including multiple pairs of successive signals.

31. (currently amended) The method of claim 30 wherein the ~~system~~ time delay estimator comprises a passive time delay estimation system.

-12-

32. (original) The method of claim 27 wherein the plurality of signals propagate through a predetermined transmission medium within the environment, the predetermined transmission medium being one of a fluid, the earth, and living tissue.

33. (original) The method of claim 27 further including the step of performing one or more preprocessing techniques on one or more of the plurality of signals by a signal processor included in the time delay estimator, thereby facilitating a determination of the temporal location of the one or more signals.

34. (original) The method of claim 33 wherein the temporal location of the one or more signals corresponds to a prominent feature of the one or more signals, the prominent feature being one of a signal peak, a signal valley, a signal energy, and a signal zero crossing.

35. (original) The method of claim 33 wherein the preprocessing techniques include at least one of a first technique including determining an absolute value of at least one of the plurality of signals, a second technique including match filtering at least one

-13-

of the plurality of signals, and an instantaneous envelope detection technique.

36. (canceled)

37. (currently amended) The method of claim 36—27 wherein the multiple second time delay estimates are substantially uniformly distributed among remaining ones of the bins.

38. (original) The method of claim 27 wherein the plurality of signals comprises one of sonar signals, seismic signals, ultrasonic signals, acoustic signals, and electromagnetic signals.

39. (original) The method of claim 27 further including the steps of receiving representations of the plurality of signals by a beamformer, and providing beams corresponding to the plurality of signals to the time delay estimator.

40. (currently amended) A method of performing time delay estimation of signals propagating through an environment, comprising the steps of:

-14-

transmitting multiple signals through the environment by a transmitter, wherein the transmitted signals travel through the environment until they strike at least one object, thereby generating multiple signals reflected from the object;

receiving the multiple reflected signals by one or more sensors;

receiving representations of the transmitted signals by a time delay estimator;

measuring time delays between multiple pairs of signals by the time delay estimator, each pair comprising a respective reflected signal and a representation of a respective transmitted signal; ~~and~~

generating time delay estimation data from the measured time delays by the time delay estimator,

wherein at least some of the time delays between the multiple pairs of signals are measured at different points in time;

analyzing the time delay estimation data by a data analyzer;

generating a statistical distribution of the time delay estimates from the time delay estimation data; and

calculating at least one of the mean, the median, and the mode of the time delay estimation distribution,

-15-

wherein the statistical distribution of the time delay estimates comprises a plurality of bins, the plurality of bins including a central bin, and

wherein at least one first time delay estimate is associated with the central bin and multiple second time delay estimates are distributed among remaining ones of the bins.

41. (original) The method of claim 40 wherein, in the event a degree of noise accompanies the reflected signals, at least some of the noise is non-correlated.

42. (canceled)

43. (currently amended) The method of claim 40 wherein the ~~system~~ time delay estimator comprises an active time delay estimation system.

44. (original) The method of claim 40 wherein each transmitted signal comprises a sonar ping, and each reflected signal comprises a sonar echo.

-16-

45. (original) The method of claim 40 wherein the multiple transmitted signals propagate through a predetermined transmission medium within the environment, the predetermined transmission medium being one of a fluid, the earth, and living tissue.

46. (original) The method of claim 40 further including the step of performing one or more preprocessing techniques on one or more of the reflected signals by a signal processor included in the time delay estimator, thereby facilitating a determination of the temporal location of the one or more reflected signals.

47. (original) The method of claim 46 wherein the temporal location of the one or more reflected signals corresponds to a prominent feature of the one or more reflected signals, the prominent feature being one of a signal peak, a signal valley, a signal energy, and a signal zero crossing.

48. (original) The method of claim 46 wherein the preprocessing techniques include at least one of a first technique including determining an absolute value of at least one of the plurality of signals, a second technique including match filtering at least one

-17-

of the plurality of signals, and an instantaneous envelope detection technique.

49.   (canceled)

50.   (currently amended) The method of claim 49 40 wherein the multiple second time delay estimates are substantially uniformly distributed among remaining ones of the bins.

51.   (original) The method of claim 40 wherein the plurality of signals comprises one of sonar signals, seismic signals, ultrasonic signals, acoustic signals, and electromagnetic signals.

52.   (currently amended) A method of performing time delay estimation of signals propagating through an environment, comprising the steps of:

transmitting multiple signals through the environment by a transmitter, wherein the transmitted signals travel through the environment until they strike at least one object, thereby generating multiple signals reflected from the object;

receiving the multiple reflected signals by one or more sensors;

-18-

receiving representations of the transmitted signals by a time delay estimator;

measuring time delays between multiple pairs of signals by the time delay estimator, each pair comprising a respective reflected signal and a representation of a respective transmitted signal;

generating time delay estimation data from the measured time delays by the time delay estimator,

wherein at least some of the time delays between the multiple pairs of signals are measured at different points in time;

~~The method of claim 40 further including the steps of~~ receiving representations of the reflected signals by a beamformer~~,~~; and

~~to provide~~ providing beams corresponding to the reflected signals to the time delay estimator by the beamformer.

53-66.   (canceled)

-19-